


Ein- und Mehrschichten-Filterbehälter

GOSLAR



Diese Zeichnung zeigt einen Goslar D 800 / Bauform I

Typenreihe GOSLAR	Artikel-Nr.	70.600.00	600	2150	2450	220	280/450	800	1350	130	1 "	4	50	—	150/50	
	Durchmesser in mm	1200	1000	2300	2600	220	280/450	800	1350	160	1 "	4	100	40	150/50	
	Gesamthöhe in mm	2400	2250	2550	220	280/450	800	1350	130	130	1 "	4	65	—	150/50	
	Gesamthöhe in mm	2700	2550	220	280/450	800	1350	130	130	130	1 "	4	110	50	150/50	
	Gesamthöhe in mm	350/450	220	280/450	800	1350	130	130	130	130	1 "	4	110	50	150/50	
	Service- öffnung DN	400	800	1350	130	130	130	130	130	130	130	1 "	4	110	50	150/50
	Mannloch zyl. Mantel DN	1000	800	1350	130	130	130	130	130	130	130	1 "	4	110	50	150/50
	OKFF- Mann- loch in mm	1350	800	1350	130	130	130	130	130	130	130	1 "	4	110	50	150/50
	Rein- wasser in mm	1350	800	1350	130	130	130	130	130	130	130	1 "	4	110	50	150/50
	Rein- wasser in mm	170	160	130	130	130	130	130	130	130	130	1 "	4	110	50	150/50
N	OKFF- Rein- wasser in mm	DN 50	1 "	1 "	1 "	1 "	1 "	1 "	1 "	1 "	1 "	4	110	50	150/50	
F	Ent- lüftung DN/R	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
I	Tank- lager Fuße	Stück	Stück	Stück	Stück	Stück	Stück	Stück	Stück	Stück	Stück	Stück	Stück	Stück	Stück	Stück
L/M	Rein- wasser DN	110	100	65	50	50	50	50	50	50	50	50	50	50	50	50
P	Luft- spül- ung DN	50	40	—	—	—	—	—	—	—	—	—	—	—	—	—
G/H	Schauglas DN	150/50	150/50	150/50	150/50	150/50	150/50	150/50	150/50	150/50	150/50	150/50	150/50	150/50	150/50	150/50